



Ölschaugläser



Ölstandsaugen GP1

Material: Stahl verzinkt inkl. NBR Dichtung

Temperatur: max. 120 °C (optional mit Viton Dichtung bis max. 160 °C)

Betriebsdruck: max. 5 bar

Reflektor: mit weiß reflektierender Oberfläche



Artikelnummer	Gewinde	Ø D [mm]	Ød [mm]	a [mm]	b [mm]	c [mm]	SW [mm]
91201.01	G3/8"	25	11,5	19	10	9	22
91201.02	G1/2"	30	14,5	19	10	9	27
91201.03	G3/4"	35	20,5	19	10	9	32
91201.04	G1"	45	26,5	21	11	10	41
91201.05	G1 1/4"	55	34,5	22	12	10	50
91201.06	G1 1/2"	61	40,5	22	12	10	55
91201.07	G2"	77	48,5	24	14	10	70
91201.21	M16 x 1,5	26	11,5	19	10	9	24
91201.22	M20 x 1,5	30	14,5	19	10	9	27
91201.23	M24 x 1,5	33	17,5	19	10	9	30
91201.24	M27 x 1,5	35	20,5	19	10	9	32
91201.26	M33 x 1,5	45	26,5	21	11	10	41
91201.27	M36 x 1,5	45	26,5	21	11	10	41
91201.28	M42 x 1,5	55	34,5	22	12	10	50
91201.29	M48 x 1,5	61	40,5	22	12	10	55
91201.30	M52 x 1,5	66	40,5	22	12	10	60
91201.31	M60 x 2	77	48,5	24	14	10	70